

PvBlack X290/BP290

特种炭黑 Special carbon black

简介 introduction:

特种炭黑 PvBlack X290/BP290 设计用于水性浆、通用色母等，为以上提供优异分散性、蓝相、中等黑度。Special carbon black PvBlack X290/BP290 is designed for use in water-based pulps, general purpose masterbatches, etc., providing excellent dispersion, blue phase, and medium blackness.

理化性质 Physical and Chemical Properties	参数 parameter
外观 Appearance	粉末 powder/粒状 granulous
平均原生粒径 Average original particle size (nm)	25±1
BET 比表面积 BET Specific surface area (m ² /g)	120±10
DBP 吸油值 DBP Oil Absorption (cc/100g)	50±5
相对着色, IRB#3(%) Tinting Strength	120±5
挥发份 Volatile matter (%)	1.0±1
PH 值	8.5±0.5

应用与特性 Application and characteristics:

- ◆ 高分散 High Dispersion
- ◆ 蓝相 blue phase
- ◆ 中等黑度 Medium blackness

推荐应用 Recommended application:

用于水性浆、通用色母

For water-based pastes, general color masterbatches

包装 packing: 10KG/Bag、20KG/Bag

备注: 本数据资料的提供出于诚意, 仅供参考, 需要由您自己测试并决定是否适合您的用途, 对我们产品的应用和处理以及您制造的最终产品都处于我们的控制之外, 我们无法承担保证和义务。

PS:The Data above is provided in good faith,FYI.

工厂地址: 新疆胡杨河市胡杨经济技术开发区车排子西路 3 号

公司地址: 东莞市常平镇桥沥南北路 25 号

电话: +86 (0) 755 23246611; 13510821649

传真: +86 (0) 755 29467129

邮箱: texong@163.com 网址: www.texong.com